



EOUV.MH10678 Dielectric Mediums

[Page Bottom](#)[Print-friendly version](#)[Questions?](#)[Previous Page](#)

Dielectric Mediums

[See General Information for Dielectric Mediums](#)

COOPER POWER SYSTEMS INC
1900 E NORTH ST
WAUKESHA, WI 53188 USA

MH10678

"Envirotemp® FR3". Classed 4 to 5 less hazardous than paraffin oil in respect to fire hazard. Flash point (closed cup) 255 C (491 F). Fire point 358 C (676 F). Ignition temperature 428 C (802 F).

"R-Temp Fluid." Classed 4 to 5 less hazardous than paraffin oil in respect to fire hazard. Flash point (closed cup) 268.3 C (515 F). Fire point 310.6 C (591 F). Ignition temperature 331 C (627.8 F).

[Last Updated](#) on 2004-04-16

[Page Top](#)[Notice of Disclaimer](#)[Questions?](#)[Previous Page](#)[UL Listed and Classified Products](#)[UL Recognized Components](#)[Products Certified for
Canada](#)

This page and all contents are Copyright © 2005 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2005 Underwriters Laboratories Inc.®"